

PTZ 22X EXT DOME

PTZ140F

**540
TVL**

3.9-85.5
mm

VARI-F

22x


355°


**1
LUX**


New attractive, low cost PTZ for External Use



Features

- ✓ 540 TVL Colour
- ✓ 22 x Optical Zoom
- ✓ Pan 9 Deg/Sec
- ✓ 355 Deg Rotation
- ✓ 9 Deg/Sec Tilt Speed
- ✓ Multi-Protocol

Description

This attractive 22 x zoom PTZ is designed for external use and has a die cast aluminium case and silver dome cover.

Compatible with our great value keyboard such as the PTZ700, PTZ730 and PTZ715.

Disclaimer

The technical specifications contained are given in good faith as being accurate but due to a continued program of improvement may change from time to time without notice. We apologise for any inconvenience due to changes of specification or errors and omissions within this document. Copyright

PTZ 22X EXT DOME

PTZ140F

**540
TVL**

**3.9-85.5
mm
VARI-F**

22x


355°


**1
LUX**


Specifications

Image Sensor	1/4" Colour
Resolution	540 TVL
Lens Type	3.9-85.8mm
Image Output	1 Volt Peak-Peak 75 ohm
Min. Illumination	1 Lux
Input Voltage	24V AC
Current Consumption	1.25 Amp
Signal to Noise Ratio	+46db
Gain Control	Automatic
Protocol	Pelco P & D
Other Protocols	Multi-Protocol
Bracket	Supplied
Build	Aluminium
White Balance	Auto
Optical Zoom	22 x
Pan Speed	9deg/sec
Tilt Speed	9deg/sec
*Extras	360deg Continuous Rotation
Dimensions	Dome Dia 230mm

Disclaimer

The technical specifications contained are given in good faith as being accurate but due to a continued program of improvement may change from time to time without notice. We apologise for any inconvenience due to changes of specification or errors and omissions within this document. Copyright