

EXT HI-SP 27X PTZ SYSTEM

PTZ800K

An attractive modern PTZ dome - Standard Speed - 27x zoom +NiteDevil - 500TVL+ looks great on modern buildings!



Features

- ✓ 270x Zoom (27x Optical, 10x Digital)
- ✓ High Resolution 500TVL
- ✓ High-speed pan 100 degs/sec
- ✓ IP66 Weatherproof
- ✓ NiteDevil
- ✓ 6 Tours & 128 presets
- ✓ Endless Rotation
- ✓ True Day-Night Motorised Filter
- ✓ High-speed tilt 40 degs/sec
- ✓ Multi-protocol

Description

In some instances a traditional CCTV head is an advantage over a modern PTZ dome design, as it stays drier in very wet conditions especially with the addition of a wiper.

The PTZ800J is aimed at being a true alternative to a modern PTZ dome for mission critical installs with its near speed-dome performance and features.

Disclaimer

The technical specifications contained are given in good faith as being accurate but due to a continued program of improvement may change from time to time without notice. We apologise for any inconvenience due to changes of specification or errors and omissions within this document. Copyright

EXT HI-SP 27X PTZ SYSTEM PTZ800K



With a rotational speed of up to 100°/second and tilt at 40°/second in response to a preset or an alarm input it doesn't miss a thing.

Small, compact and tough the die-cast aluminium camera housing is finished in an attractive ivory colour with a built in window wiper to prevent dirt and rain from distorting the camera's image. This kit is fully IP66 rated for external use but can also be used internally in large covered areas such as factories, warehousing or shopping centres.

With features such as alarm inputs, 360° rotation, presets, tours and a choice of camera module the PTZ800J is a great option for customers requiring a traditional style high performance system.

The head is multi-protocol (16+) including the favoured Pelco P & D protocols so it can be controlled through any of our keyboards opposite or by a capable DVR or Network Video Server such as our Alien range of DVRs.

Disclaimer

The technical specifications contained are given in good faith as being accurate but due to a continued program of improvement may change from time to time without notice. We apologise for any inconvenience due to changes of specification or errors and omissions within this document. Copyright

EXT HI-SP 27X PTZ SYSTEM

PTZ800K



Specifications

Image Sensor	1/3" Colour
Resolution	500 TVL
Image Output	1 Volt Peak-Peak 75 ohm
Min. Illumination	0.001 Lux
Day/Night Function	Electronic & Mechanical
Audio	N/A
Input Voltage	24V AC
Video Connection	BNC Socket
Power Connection	Terminal Strip
Protocol	Pelco P & D
Other Protocols	14 others
Bracket	Supplied
Finish	Ivory
Build	Metal Case
Optical Zoom	27x
Digital Zoom	10 x
Pre-sets	128
Tours	6
Pan Speed	Standard 40Deg / Sec Pre-Set 100 Deg / S
Tilt Speed	40 Deg / Sec
Dimensions	(H)410mm x (L)340mm x (W)150mm

Disclaimer

The technical specifications contained are given in good faith as being accurate but due to a continued program of improvement may change from time to time without notice. We apologise for any inconvenience due to changes of specification or errors and omissions within this document. Copyright